

US005737115A

United States Patent [19]

Mackinlay et al.

[11] Patent Number:

5,737,115

[45] Date of Patent:

Apr. 7, 1998

[54] ADDITIVE COLOR TRISTATE LIGHT VALVE TWISTING BALL DISPLAY

[75] Inventors: Jock D. Mackinlay, Palo Alto;

Maureen C. Stone, Los Altos, both of

Calif.

[73] Assignee: Xerox Corporation, Stamford, Conn.

[21] Appl. No.: 573,922

[56]

[22] Filed: Dec. 15, 1995

282; 349/112, 142, 87, 94, 117, 188

References Cited

U.S. PATENT DOCUMENTS

Re. 34,942	5/1995	Clark et al 349/188
4,126,854	11/1978	Sheridon 345/107
4,143,103	3/1979	Sheridon 264/4
4,261,653	4/1981	Goodrich 359/296
4,268,413	5/1981	Dabisch 252/408
4,299,880	11/1981	Arens 428/304
4,374,889	2/1983	Arens 428/207
4,418,098	11/1983	Maistrovich 427/161
4,438,160	3/1984	Ishikawa et al 427/214
4,500,172	2/1985	Gagnon et al 349/9
4,663,083	5/1987	Marks 252/583
4,688,900	8/1987	Doane et al 349/87
4,695,528	9/1987	Dabisch et al 430/290
4,729,687	3/1988	Arens 401/198
4,810,431	3/1989	Leidner 264/15
4,837,071	6/1989	Tagoku et al 428/195
4,877,253	10/1989	Arens 273/240
4,890,902	1/1990	Doane et al 349/94
4,919,521	4/1990	Tada et al

(List continued on next page.)

OTHER PUBLICATIONS

"Sharp Develops a New ECB Reflective STN Display— ('New Hysteresis') Color LCD", Press Release No. 95–049, Sharp Corporation, Osaka, Japan, Oct. 9, 1995. "Technical Report: Reflective-Type LCD Technology Trends", Section 3 subtitled Polarizer-Type LCD Technology Trends obtained via the Internet from Sharp Corporation's World Wide Web site (http://www.sharp.co.jp/sc/library-e/lcd/lcd3_htm) on Jul. 12, 1996.

Business Wire (available through Dialog, File 610), "S.I.P. and ETIP to jointly develop the world's first eraseable and reusable paper for printing," Aug. 19, 1991.

(List continued on next page.)

Primary Examiner—Loha Ben Attorney, Agent, or Firm—Alexander E. Silverman

[57] ABSTRACT

A tristate light valve ball for an electrical twisting ball device composed of spheroidal balls rotatably disposed in an elastomer substrate. The ball is composed of segments arrayed substantially parallel to one another, each segment being adjacent to at least one other segment and to no more than two other segments. Adjacent segments are adjoined to one another at substantially planar interfaces. The segments include: a first, interior, nontransparent segment having a first optical modulation characteristic; a second exterior, transparent segment, adjacent to the first segment and having a second optical modulation characteristic; a third, interior, nontransparent segment having a third optical modulation characteristic; and a fourth, exterior, transparent segment adjacent to the third segment. For example, the ball can be made with a black first segment adjacent to a white third segment, surrounded on either side by clear second and fourth exterior segments. The ball has an anisotropy for providing an electrical dipole moment, the electrical dipole moment rendering the ball electrically responsive such that when the ball is rotatably disposed in a nonoscillating electric field while the electrical dipole moment of the ball is provided, the ball tends to rotate to an orientation in which the electrical dipole moment aligns with the field. Also disclosed are: a material made up of a substrate layer in which are disposed the aforementioned balls, with a colored backing joined to a rear surface of the layer; and a method for using a device incorporating the balls.

20 Claims, 32 Drawing Sheets

